

OCXO - 20.7 X 13.08 X 10.8mm 14PIN DIP FULL SIZE



FEATURES:

- WIDE FREQUENCY RANGE
- LONG TERM AGING
- LOW COST

RoHS
Compliant



MODEL	OX - F
FREQUENCY RANGE	1 MHz to 100 MHz
FREQUENCY ACCURACY	± 0.5 ppm (central control voltage)
FREQUENCY STABILITY vs. TEMPERATURE	See Part numbering Guide
AGING	First year ± 0.5ppm, 10 years ± 3 ppm max.
SHORT TERM STABILITY	1 x 10 ⁻¹⁰ / ms
OUTPUT TYPE AND LOAD CHARACTERISTICS	CMOS (15pF), Clipped sine wave (10KΩ/10pF), or Sinewave (50Ω)
SUPPLY VOLTAGE	+3.3 VDC or +5.0 VDC
FREQUENCY STABILITY vs. LOAD CHANGE ± 10%	± 0.02 ppm max.
FREQUENCY STABILITY vs. VOLTAGE ± 5%	± 0.02 ppm max.
SUPPLY CONSUMPTION	1.6W(max.) during warm-up; 0.6W(max.) when static
WARM-UP TIME	± 0.5 ppm, < 3 minute
ADJUSTABLE FREQUENCY RANGE	± 5.0 ppm min.
CONTROL VOLTAGE RANGE	0 ~ 5 V, N/C option available
SLOPE	Positive
LINEARITY	± 10 %
PHASE NOISE (5V)	10Hz, -100dBc/Hz typical
	100Hz, -135dBc/Hz typical
	1KHz, -150dBc/Hz typical
	10KHz, -155dBc/Hz typical
STORAGE TEMPERATURE RANGE	-55 °C ~ +125 °C



Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.