





- WIDE FREQUENCY RANGE
- INDUSTRY STANDARD PACKAGE
- CAPABLE OF REFLOW
- CUSTOM SPECIFICATION AVAILABLE

RoHS
Compliant



MODEL	FREQUENCY	TUNING VOLTAGE	PHASE NOISE @10KHz	2nd HARMONICS	POWER
TEV-5V156	140~172 MHz	1.5~3.5 V	-113 dBc/Hz	-18 dBc	0 dBm
TEV-5V280A	274~286 MHz	0.5~4.5 V	-110 dBc/Hz	-13 dBc	0 dBm
TEV-5V325	300~350 MHz	0.5~4.5 V	-108 dBc/Hz	-15 dBc	5 dBm
TEV-5V910A	860~960 MHz	1.0~4.0 V	-100 dBc/Hz	-30 dBc	4 dBm
TEV-5V1150	1090~1210 MHz	0.5~4.5 V	-102 dBc/Hz	-17 dBc	7 dBm
TEV-5V1650	1500~1800 MHz	0.5~4.5 V	-96 dBc/Hz	-20 dBc	1 dBm
TEV-5V2000	1700~2300 MHz	0~5 V	-95 dBc/Hz	-23 dBc	3 dBm
TEV-5V2140C	2050~2250 MHz	0.5~4.5 V	-97 dBc/Hz	-22 dBc	0 dBm
TEV-5V2400A	2300~2500 MHz	1~4 V	-97 dBc/Hz	-24 dBc	2 dBm
TEV-5V2545A	2395~2695 MHz	0.5~4.5 V	-97 dBc/Hz	-23 dBc	5 dBm
TEV-5V2740	2720~2760 MHz	1~4 V	-91 dBc/Hz	-35 dBc	1 dBm



Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.