

- 110.00 MHz IF SAW Filter / 20.27 MHz Bandwidth
- Revision 0: 09. May 2008


## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operation Temperature Range	°C	0	-	60
Storage Temperature Range	°C	-30	-	80
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	D1			
Length x Width	mm <sup>2</sup>	-	20.0 x 9.8	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	110.00	-
Insertion Loss at Fo	dB	-	20.0	23.0
Group Delay Variation (Fo±9.75MHz)	ns	-	40	80
Absolute Delay	us	-	2.38	-
Passband Ripple (Fo±9.75MHz)	dB	-	0.54	1.00
Bandwidth at -1dB	MHz	-	20.27	-
Bandwidth at -3dB	MHz	-	20.54	-
Bandwidth at -40dB	MHz	-	21.73	-
Ultimate Rejection	dB	-	52	-
Temperature coefficient	ppm/°C	-	-72	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① TRANSKO: Brand
- ② TA11020B: Model Name
- ③ X : Date Code (Year)
- ④ Y : Date Code (Month)
- ⑤ Z : Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output

## Testing Environment





Test Fixture & Values	
Input	L1=68nH, C1=18pF
Output	L2=68nH, C2=22pF
Source/Load Impedance	50 $\Omega$

## Frequency Characteristics

### Frequency Response



**Bandwidth at -1.0 dB**

**Bandwidth at -3.0 dB**



**Bandwidth at -40.0 dB**



**Wide-Band**



**Frequency Response**

**Ripple Variation Fo±9.75MHz**

**Group Delay Variation Fo±9.75MHz**



**Smith Chart**

**VSWR**

