

- 90.0 MHz IF SAW Filter / 47.20 MHz Bandwidth
- Revision 0: 07 Oct. 2011

## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-10	-	50
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	90.00	-
Insertion Loss at Fo	dB	-	20.00	22.00
Group Delay Variation at Fo ± 22.50 MHz	nsec	-	22	50
Absolute Delay at Fo	usec	-	1.02	1.15
Passband Ripple Variation at Fo ± 22.50 MHz	dB	-	0.50	1.00
Bandwidth at -1dB	MHz	46.80	47.20	-
Bandwidth at -3dB	MHz	-	48.25	-
Bandwidth at -40dB	MHz	-	53.00	53.40
Ultimate Rejection	dB	35	42	-
Temperature Coefficient	ppm/°C	-	-86	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL09047A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

## Testing Environment




Test Fixture & Values	
Input	L1 = 68nH
Output	L2 = 82nH, C1=240pF
Source/Load Impedance	50 Ω

## Frequency Characteristics


### Frequency Response

Operating Temperature : +25 °C


**Bandwidth at -1.0 dB**




**Bandwidth at -3.0 dB**



**Bandwidth at -30.0 dB**





**Bandwidth at -40.0 dB**



**Frequency Response**

**Ripple Variation Fo±22.50MHz**

**Group Delay Variation Fo±22.50MHz**



**Smith Chart**

**VSWR**

