

MINIATURE CERAMIC SMD CRYSTAL (4.0 x 2.5 x 0.75mm)

FEATURES:


- WIDE FREQUENCY RANGE
- LOW COST SMD PACKAGE
- LOW PROFILE / SUITABLE FOR REFLOW



■ SPECIFICATION

FREQUENCY RANGE	12.000MHz ~ 50.000MHz
FREQUENCY TOLERANCE @ 25°C	±10ppm ~ ±50ppm (See P/N guide for other options)
FREQUENCY STABILITY	±10ppm ~ ±50ppm (See P/N guide for other options)
OPERATING TEMPERATURE RANGE	STD: 0°C ~ 70°C, Option: -40°C ~ 85°C (See P/N guide for other options)
STORAGE TEMPERATURE RANGE	-55°C ~ 125°C
LOAD CAPACITANCE	STD: 12pF (See P/N guide for other options)
SHUNT CAPACITANCE	5.0pF max.
INSULATION RESISTANCE	500MΩ min. @ 100V _{DC} ± 15V _{DC}
DRIVE LEVEL	100μW ~ 200μW max. – contact factory for higher drive level
AGING @ 25°C ± 3°C	±3.0ppm / 1 st year max.
EQUIVALENT SERIES RESISTANCE	12.000MHz ~ 16.000MHz: 80Ω max. 16.001MHz ~ 21.000MHz: 60Ω max. 21.001MHz ~ 50.000MHz: 50Ω max.
OPERATION MODE	AT cut, Fundamental

■ PACKAGE DIMENSIONS




* Package 1 and 2 are provided interchangeably based on material availability.
** Different chamfer location between package 1 and 2.

Unit : mm


Pin Configuration	
1	Xtal
2	GND
3	Xtal
4	GND

■ SOLDER PATTERN



Unit :mm

■ REFLOW PROFILE



Note: Consult factory for detail

■ PART NUMBERING GUIDE

CS42 – F		30	50	HM	12	– 40.000M	– TR
Mode F: Fundamental		Stability 00: ± 100ppm 50: ± 50ppm 25: ± 25ppm 15: ± 15ppm 10: ± 10ppm XX: Two digit for Stability		Load Capacitance 08: 8pF 10: 10pF 12: 12pF 16: 16pF 18: 18pF S: Series		Other Options TR: Tape and reel	
Tolerance @ 25°C 00: ± 100ppm 50: ± 50ppm 30: ± 30ppm 25: ± 25ppm 10: ± 10ppm XX: Two digit for Tolerance		Operating Temperature A: -55 F: -20 M: 70 S: 100 B: -50 G: -10 N: 75 T: 105 C: -40 H: 0 P: 80 U: 125 D: -35 J: 50 Q: 85 X: custom E: -30 K: 60 R: 90					
		Frequency M: MHz					

Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.